

Integrated FTTH Unit Multipack-F



ALLINONE+ : Integrated 6 function in one unit

{stripping, cleaning, cleaving and sleeving
+ Optical power meter and V.F.L(Visual Fault Locator)}

Benefits and Features

- Integrated 6 Function in One Unit
- Built-in Power Meter and Fault Locator (PCT/KR2013/001243)
- Compatible with Fusion Splice-On Connector(SOC) in accordance with the Industrial Standard



Stripping
(No Cracks on Fiber)



Cleaning



Cleaving



Power Meter & Fault Locator

Specification

CATEGORY	DESCRIPTION
Stripping	
Stripped length	27mm
Fiber Diameter	0.25 ~ 0.9mm
Blade Lifetime	More than 100,000
Motor Lifetime	1,000,000
Fiber Type	Single Fiber
Tensile Strength Test	More than 3Kgf
Heating Time	2.2sec
Heating Temperature	130°C
Cleaning	
Method	Air-pump
Cleaning Spec.	13ml / 100 times
Cleaning Liquid	Alcohol
Cleaving	
Cleaving Length	8mm
Blade Lifetime	50,000
Sleeve Heating	
Temperature	190°C
Time	30sec, 70sec(Connector)
Sleeve Length	60mm
Fiber Type	250, 900, 2 ~ 4 Connector 4Type(SC, FC, LC, ST)
Using Spec.	
Dimension	145x137x98mm
Weight	1.2kg