

Stand-Alone Devices

Auto Stripper



- High Quality
- High Productivity
- More Convenience

CATEGORY	DESCRIPTION
Applicable	250 ~ 900 μ m
Fiber Counts	Single to 12ct
Stripped length	30mm
Heating temp.	60 $^{\circ}$ C ~ 140 $^{\circ}$ C
Temp. Setting Step	9 Steps
Heating Time	2 ~ 7sec
Time Setting Step	5 Steps
Power	DC 12V
Dimension	154x64x76mm
Weight	750g

Window Stripper



- No Fiber Crack & Keep High Tensile Strength
- Chemical Strip Draw-backs Resolved

CATEGORY	DESCRIPTION	
Stripped length	2 ~ 120mm	2 ~ 60mm
Applicable cable diameter	250 μ m	
Fiber Coating Material	UV Coated Fiber	
Stripping time	20mm / sec	
Power	DC 12V	
Dimension	190x64x76mm	
Weight	800g	

Ultrasonic Cleaner IFC-24



- Automatic touch operation
- Compatible fiber holder adaptor(16 & 20mm)
- Fiber optic connector adaptation: FC/ST, SC, LC, MU, MT-RJ connector
- High frequency ultrasonic action

CATEGORY	DESCRIPTION
Fiber Mode	125 μ m
Coating Diameter	250 ~ 900 μ m
Rinsing Liquid	Alcohol
Cleaning Time(1 Cycle)	1 ~ 3sec
Power & Voltage	15W & DC 12V 10%
Dimension	115x75x95mm
Weight	560g